



Order Code: KYBAC260UP-BKGR

Accuratus 260 GERMAN - Full Layout Professional Keyboard with Contoured Touch Typing Keys

About

The 260 is a firm favourite due to its stylish looks, durability and positive feedback keys. In a full size German key layout with full height shaped keys on a contoured inclined base, the 260 provides hours of comfortable typing. The 260 offers full height keys which are contoured to shape your fingers, which also slope up towards the back of the keyboard offering excellent touch typing capabilities. Available in many language layouts, lowercase, high visibility, USB or PS/2 interfaces and with or without a 2 port USB2.0 hub, we have every option covered.

Whether it be for home, office, school or elsewhere, you will not be disappointed with the Accuratus 260, the original and professional typing keyboard.

Specifications

- USB & PS/2 combo connection
- German key layout (other Language variants are available)
- Black case and keycaps with white key legends
- Laser etched key legends for long life and durability
- Full height contoured keys for comfortable typing, the keys gradually slope up towards the back of the keyboard to offer excellent touch typing.
- Keycaps are finger tip shaped to allow for ease of use
- Standard keyboard size
- Full keyboard key layout with numeric keypad
- Membrane key technology
- Responsive tactile feedback keys
- Fold out feet to provide keyboard tilt
- Status LED's for Caps, Num & Scroll Lock)
- Also available in Many other languages; Chinese, Cyrillic Russian, French, German, Hong Kong, Dutch, Italian, Japanese, Norwegian, Polish, Spanish, Swedish / Finnish, Swiss, UK.

Physical Specifications

- Dimensions: 456 x 168 x 32 mm (l x w x h)
- Weight: 713g
- Cable Length: 1.7M

Accessories

- A matching mouse is available with the same colour and texture as the keyboard. Part number MOUAC3331-BLK
- A flexible keyboard cover is available to fit over the keyboard, shaped around the keys for dusty and dirty environments, it will also protect the keyboard from liquid and spills. Part number : VIZ-260EURO-SEEL



Other Specifications

- ESD rating : Contact discharge 2K ~ 4K
- ESD rating : Air discharge 2K ~ 8K
- Operating temperature : 0 to +55°C
- Storage temperature : -20 to +60°C

Electrical Requirements

- Max rating : DC 6V, 0.3A
- Recommendation : DC 5V, 0.1A
- Power supply voltage : +5v +/-5%

Reliability

- MTBF : 16,000 hours approximately

Compliances

- CE, FCC, RoHS

